EVALUATION REPORT ON TECHNICAL BIDS OPENED ON 08-10-2016 FOR THE PROCUREMENT OF CARBON DIOXIDE INCUBATOR WITH SHAKER, TENDER ENQUIRY NO. PC/DF(R&T)-VI/2016-17

Sr. #	Approved Specification of the Department	Name of the Firm & Address	Specifications/Brand/Model quoted by the Firm	Remarks/Recommendations with reasons
1.	 Supply Voltage: 220 volts Carbon dioxide incubator with built in shaker Digital control panel Temperature range: 5-55 °C 	Rays Technologies 1/I, Block F, Near Main Market, Gulberg-II, Lahore- 54660, Pakistan. Tel: 0092-42- 35753903	Operated on 220 volts With orbital shaker specially designed for shaking incubator Multifunctional Digital Microprocessor PID controller Temperature range: ambient 8 to +50 °C	The quoted specifications of this firm for carbon dioxide incubator with shaker do not fulfill/qualify the standardized/approved specifications because: The Carbon Dioxide
	 Shaking speed: Adjustable between 30-200 RPM Infrared CO₂ sensor CO₂ Range: 0.1 to 20 % CO₂ accuracy: ± 0.1 % Capacity > 150 L With all accessories including two carbon dioxide cylinder etc. Country of origin: Western Europe, USA, Japan, or equivalent Warranty: Two year warranty (service and parts) 	0	 20-200 RPM Digital Electronic CO₂ control with automatic zeroing (infrared measuring system) Adjustable Range 0-20 % CO₂ accuracy: ± 0.1 % Capacity 153 liter capacity Complete with three stainless steel shelves, With two CO₂ gas cylinders (Locally supplied) Model INC-153med, Memmert Germany Two year from the date of installation by our qualified engineer. 	Incubator is not with built- in shaker The firm is not recommended for the purchase of carbon dioxide incubator with shaker. Director Fine (PBD) Headquarter, (PBD)

SENIOR CHEMIST

Fisherica Desearch Institute

AHORE

Fisheries Research & Training Institute, Lahore. PRINCIPAL CHEMIST
FISHERIES RESEARCH & TRAINING
INSTITUTE LAHORE.

Director Fisheries
Research & Training Institute
LAHORE

2.	 Supply Voltage: 220 volts Carbon dioxide incubator with built in shaker Digital control panel Temperature range: 5-55 °C Shaking speed: Adjustable between 30-200 RPM Infrared CO₂ sensor CO₂ Range: 0.1 to 20 % CO₂ accuracy: ± 0.1 % Capacity > 150 L With all accessories including two carbon dioxide cylinder etc. Country of origin: Western Europe, USA, Japan, or equivalent Warranty: Two year warranty (service and parts) 	Scientific Technical Corporation (Pvt) Ltd. LG-2, 3, 4 & 6 Queed's Center, 33- Shahrah-e-Fatima Jinnah (Queens Road) Lahore- 54000 (Pakistan)	 Power: 220 V, 50/60 Hz CO2 Incubator with orbital Shaker Digital control panel 5 °C to 55 °C (5 °C above ambient to 30 °C max. ambient) 30 -300 RPM (Shaker) Infrared Single source CO2 Range: 0.1 to 20 % CO2 accuracy: ± 0.1 % 7 cu.ft./200Lit With all standard accessories including two carbon dioxide cylinders (local arranged) Model: NU-5800E NUAIRE INC., USA. 02 years from the date of supply (warranty does not cover damages due to misuse, accidental damage or damage from a power surge or due to natural disaster) 	The quoted specifications of this firm for carbon dioxide incubator with shaker do not fulfill/qualify the standardized/approved specifications because: • The Carbon Dioxide Incubator is not with builtin shaker The firm is not recommended for the purchase of carbon dioxide incubator with shaker.
3.	 Supply Voltage: 220 volts Carbon dioxide incubator with built in shaker Digital control panel Temperature range: 5-55 °C Shaking speed: Adjustable between 30-200 RPM Infrared CO₂ sensor CO₂ Range: 0.1 to 20 % 	Pak Glorious Enterprise, Flat # 305, Muhammadia Plaza, Gordon College Road, Rawalpindi Pakistan. Ph: +92- 51-5535591	 220 V, 50 Hz or 60 Hz Carbon dioxide incubator with shaker Digital control panel Ambient +5 °C to 60 °C temp. Speed range: 30-300 rpm Infrared CO₂ sensor CO Range: 0 % to 20 % 	The quoted specifications of this firm for carbon dioxide incubator with shaker do not fulfill/qualify the standardized/approved specifications because: • The country of origin is Korea

LAHORE.

 CO₂ accuracy: ± 0.1 % Capacity > 150 L With all accessories including two carbon dioxide cylinder etc. Country of origin: Western Europe, USA, Japan, or equivalent 	 CO₂ accuracy: ± 0.1 % at 5 % at 37 °C Capacity/Shelves: 179 Liter/3ea Supplied with 2 X CO₂ cylinders Model: NB203 XL 179Liter Direct Heat CO2 Incubator < CE Mini Shaker With Wire Remote Controller, Manufacturer: n- Biotek, Korea 	The firm is not recommended for the purchase of carbon dioxide incubator with shaker.
Warranty: Two year warranty (service and parts)	2 year with parts and labor	

SENIOR CHEMIST
Fisheries Research Institute
AHORE.

LIBRARIAN
Fisheries Research & Training Institute,
Lahore.

PRINCIPAL CHEMIST
FISHERIES RESEARCH & TRAINING
INSTITUTE LAHORE.

Director Fisheries
Research & Training Institute
LAHORE

Peputy Director Pisheries
(PSD) Headquarter,
Bepartment of Picheries
PUNJAR