# EVALUATION REPORT ON TECHNICAL BIDS OPENED ON 08-10-2016 FOR THE PROCUREMENT OF DIESEL GENERATOR (80KVA), TENDER ENQUIRY NO. PC/PM(Bbs-Lhr)-1/2016-17

ď.	Approved Specifications of the Department	Name of the Firm & Address	Specifications/Brand/Model quoted by the	Remarks/Recommendations with
	Origin  USA, Canada, Japan, UK and west Europe Capacity Prime Rating 60 KVA to 80 KVA  Heavy Duty Fabricated steel skid type based frame with anti-vibration mounting/ isolators.  Diesel fuel tank for minimum 8 hours of continuous run	Multiline Engineering Co:3-A  1, Off Airport Road Opposite, Toyta Airport Motors, Lahore Cantt.	Model-IDPU 80  Origin  Made in UK 80 KVA (Prime) & 88 KVA (Standby) Heavy Duty Fabricated steel skid type based frame with anti-vibration mounting/ isolators. Diesel fuel tank for minimum 8 hours of continuous run	This firm has quoted the specifications of Diesel Generator (80 KVA) which match the specifications of tender. Thus, this firm is RECOMMENDED for the purchase of Diesel Generator.
	Engine  Prime power rating 60 KVA to 80 KVA  Direct coupled with Alternator  Alternator  Brushless Self-excited Automatic voltage frequency		Engine Perkins 1104A-44TG2  Prime power rating 60 KVA to 80 KVA  Direct coupled with Alternator  Alternator Meccalte (UK)  Brushless Self-excited Automatic voltage frequency	

Deputy Freject Manager Delitery of Setter Estandor Services Department of Fabories Puryals, Lotore. Project Estimation Service Delivery of Better Estimation Service Department of Fisheries Purists, Labore (PED) Headquarter. Beny ment by Fisherica PUNJAR.

204

- Automatic frequency regulated
- 400/220 Volt, 3-Phase, 4 wire, 50Hz (Nominal frequency)
- · F/H type insulated

## Speed

1500RPM (minimum)

# Exhaust System

 Heavy Duty Residential Grade Silencer with flexible exhaust.

## Governor Protection

- Electric / Mechanical
- Overload Shutdown
- Short circuit shut down
- · Low oil pressure shutdown
- · High water temperature shutdown
- · Under-speed shutdown
- Over-Winding temperature shutdown
- · Over-Voltage monitor and tripping
- · Low-voltage monitor and tripping

# Monitoring/Control Pannel

- Automatic Alarm Monitor
- Under/Over voltage

- Automatic frequency regulated
- 400/220 Volt, 3-Phase, 4 wire, 50Hz (Nominal frequency)
- · F/H type insulated

## Speed

1500RPM (minimum)

## **Exhaust System**

· Heavy Duty Residential Grade Silencer with flexible exhaust.

#### Governor Protection

- Electric / Mechanical
- Overload Shutdown
- Short circuit shut down
- Low oil pressure shutdown
- · High water temperature shutdown
- Under-speed shutdown
- Over-Winding temperature shutdown
- · Over-Voltage monitor and tripping
- · Low-voltage monitor and tripping

# Monitoring/Control Pannel

- · Automatic Alarm Monitor
- Under/Over voltage

Ecour Prestor (PSD) Holidginrier.

Espartment of/Plaharian

#### Metering

- Voltmeter
- Frequency Meter
- Ampere Meter
- Hour meter

#### Batteries

- · Heavy duty Lead Acid Batteries
- · Battery Rack and Cable
- Auto battery charger

## Standard Accessories

· Technical and Operational Manual (one set in original)

#### ATS Pannel

- . ATS Pannel 3 pole for 1 WAPDA meter
- Battery Charger
- · MOR (manual over writable)
- Telemechanic Contractors
- ABB

#### Canopy

· Sound level 85db or less from one-meter distance

#### Power/ control Cable

99.99% pure cable

#### Metering

- Voltmeter
- Frequency Meter
- Ampere Meter
- Hour meter

## Batteries

- · Heavy duty Lead Acid Batteries
- · Battery Rack and Cable
- · Auto battery charger

## Standard Accessories

 Technical and Operational Manual (one set in original)

#### ATS Pannel

- ATS Pannel 3 pole for 1 WAPDA meter
- Battery Charger
- · MOR (manual over writable)
- Telemechanic Contractors
- ABB

## Canopy

· Sound level 85db or less from one-meter distance

#### Power/ control Cable

99.99% pure cable

Deputy Director Fisheria. IF &D | Heydquarter, Beparment of Fisherian PUNIAS.

	Warranty At least 1 year or 2000 hours after installation (service plus parts) Note: The nearest specification would be acceptable		Warranty At least 1 year or 2000 hours after installation (service plus parts)	
2-	Origin  USA, Canada, Japan, UK and west Europe Capacity Prime Rating 60 KVA to 80 KVA  Heavy Duty Fabricated steel skid type based frame with anti-vibration mounting/ isolators.  Diesel fuel tank for minimum 8 hours of continuous run	Shirazi Trading Co (Pvt) Ltd. 3- bank Square, Lahore.	Origin  • Model APD 66CUSA  Capacity Prime Rating 66 KVA  • Heavy Duty Fabricated steel skid type based frame with anti-vibration mounting/ isolators.  • Diesel fuel tank for minimum 8 hours of continuous run	This firm has quoted the specifications of Diesel Generator (80 KVA) which match the specifications of tender. Thus, this firm is RECOMMENDED for the purchase of Diesel Generator (Subject to provision of origin USA).
	Engine Prime power rating 60 KVA to 80 KVA  Direct coupled with Alternator Alternator Brushless Self-excited Automatic voltage frequency Automatic frequency regulated 400/220 Volt, 3-Phase, 4		Engine 4BTA 3.9 Gz Prime power rating 60 KVA  Direct coupled with Alternator  Alternator Brushless Self-excited Automatic voltage frequency Automatic frequency regulated 400/230 Volt, 3-Phase, 4	

Deputy Philad Nanager Belling of Baller Enlanden Services Department of Fish-stee Parges, Labora Project Morage Delivery of Bothe Estalizary Sorvice Department of February Purish, Labora. Lebury Director Flahert.

(P60) Head Junter.

Localiment of Flaherto

wire, 50Hz (Nominal frequency)

F/H type insulated

## Speed

1500RPM (minimum)

# Exhaust System

 Heavy Duty Residential Grade Silencer with flexible exhaust.

#### Governor Protection

- Electric / Mechanical
- Overload Shutdown
- Short circuit shut down
- · Low oil pressure shutdown
- · High water temperature shutdown
- · Under-speed shutdown
- · Over-Winding temperature shutdown
- Over-Voltage monitor and tripping
- · Low-voltage monitor and tripping

# Monitoring/Control Pannel

- Automatic Alarm Monitor
- Under/Over voltage

# Metering

- Voltmeter
- Frequency Meter

wire, 50Hz (Nominal frequency)

F/H type insulated

#### Speed

1500RPM

## **Exhaust System**

 Heavy Duty Residential Grade Silencer with flexible exhaust.

# Governor Protection

- Electric / Mechanical
- Overload Shutdown
- Short circuit shut down
- · Low oil pressure shutdown
- · High water temperature shutdown
- · Under-speed shutdown
- · Over-Winding temperature shutdown
- Over-Voltage monitor and tripping
- · Low-voltage monitor and tripping

# Monitoring/Control Pannel

- Automatic Alarm Monitor
- Under/Over voltage

# Metering

- Voltmeter
- Frequency Meter

- Ampere Meter
- Hour meter

## Batteries

- Heavy duty Lead Acid Batteries
- Battery Rack and Cable
- · Auto battery charger

#### Standard Accessories

 Technical and Operational Manual (one set in original)

#### ATS Pannel

- ATS Pannel 3 pole for 1 WAPDA meter
- Battery Charger
- MOR (manual over writable)
- · Telemechanic Contractors
- ABB

# Canopy

 Sound level 85db or less from one-meter distance

## Power/ control Cable

99.99% pure cable

# Warranty

At least 1 year or 2000 hours after installation (service plus parts)

Note: The nearest specification would be acceptable

Bapula Najed Manager

- Ampere Meter
- Hour meter

#### Batteries

- Heavy duty Lead Acid Batteries
- · Battery Rack and Cable
- · Auto battery charger

## Standard Accessories

 Technical and Operational Manual (one set in original)

# ATS Pannel

- ATS Pannel 3 pole for 1 WAPDA meter
- Battery Charger
- MOR (manual over writable)
- · Telemechanic Contractors
- ABB

# Canopy

 Sound level 85db or less from one-meter distance

## Power/ control Cable

99.99% pure cable

# Warranty

At least 1 year or 2000 hours after installation (service plus parts)

Protestanting
Develop of Better Extension Services
Department of Fatheries
Purjob, Lahora.